



300 Pond Street - Randolph, Massachusetts 02368
 TEL: 781-986-2424 FAX: 781-986-2029

Well-Rite Series Diaphragm Tanks

Product Specifications

Model #'s	Dimensions				Volume		Shipping (Box) Volume		Shipping (Box) Weight	
	Diameter		Height		gal.	liter	cubic ft.	cubic m.	lbs.	kilos
	in.	cm.	in.	cm.						
WR45	16	40.64	22	55.88	14	53	3.62	0.10	28.0	12.7
WR60	16	40.64	29	73.66	20	76	4.73	0.13	36.0	16.3
WR80	16	40.64	34.5	87.63	26	99	5.59	0.16	41.0	18.6
WR100	21	53.34	27.75	70.48	32	121	7.76	0.22	54.0	24.5
WR120	16	40.64	42.75	108.58	33	126	6.93	0.19	49.0	22.2
WR140	21	53.34	36.25	92.07	44	167	10.17	0.28	67.0	30.4
WR200	21	53.34	48	121.92	62	235	13.64	0.38	82.0	37.2
WR240	21	53.34	62	157.48	81	307	16.45	0.46	99.0	44.9
WR260	26	66.04	44.5	113.03	85	322	18.69	0.52	121.0	54.9
WR360	26	66.04	59.75	150.49	119	450	26.16	0.73	153.0	69.5

Models WR45-WR120 – 28 psi/1.9 bar pre-charge – 1" N.P.T. connection stainless steel elbow

Models WR140-WR360 – 38 psi/2.6 bar pre-charge – 1-1/4" N.P.T. connection stainless steel elbow

Maximum working pressure: WR45-WR240 – 100 psi/6.8bar • WR260-WR360 – 125 psi/7.4 bar